



## SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** 130040 - AC Self-Sealer 0040 SMMT  
**Other means of identification:**  
Not applicable (N/A)
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses: Coatings for wood. For industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**  
Valresa Coatings, S.A.  
Pol. Ind. Reva S-13 Avda. dels Gremis s/n  
46190 Riba-roja de Turia - Valencia - Spain  
Phone: +34 961669560 - Fax: +34 961668665  
safety@valresa.com  
www.valresa.com
- 1.4 Emergency phone number:** +1 772 284 5590 (Only available during office hours)

## SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
**29 CFR 1910.1200:**  
Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.  
Eye Irrit. 2A: Eye irritation, Category 2A, H319  
Flam. Liq. 2: Flammable liquids, Category 2, H225  
Skin Irrit. 2: Skin irritation, Category 2, H315  
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**  
**29 CFR 1910.1200:**  
Danger
- 
- Hazard statements:**  
Causes serious eye irritation.  
Highly flammable liquid and vapour.  
Causes skin irritation.  
May cause damage to organs through prolonged or repeated exposure (Oral).  
May cause drowsiness or dizziness.
- Precautionary statements:**  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
In case of fire: Use ABC powder extinguisher to put it out.  
Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Substances that contribute to the classification**  
N-butyl acetate; Ethyl acetate; Reaction mass of ethylbenzene and m-xylene and p-xylene ; Butanone
- Additional labeling:**
- 
- WARNING**  
This product can expose you to chemicals including methanol, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

- CONTINUED ON NEXT PAGE -

## SECTION 2: HAZARD(S) IDENTIFICATION (continued)

**2.3 Hazards not otherwise classified (HNOC):**

Not applicable (N/A)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.1 Substances:**

Non-applicable

**3.2 Mixtures:****Chemical description:** Mixture composed of additives and acrylic resin in solvents**Components:**

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name	Concentration
CAS: 123-86-4	<b>N-butyl acetate</b>	<b>25 - &lt;50 %</b>
CAS: 141-78-6	<b>Ethyl acetate</b>	<b>10 - &lt;25 %</b>
CAS: Non-applicable	<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b>	<b>5 - &lt;10 %</b>
CAS: Non-applicable	<b>Reaction mass of ethylbenzene and xylene</b>	<b>5 - &lt;10 %</b>
CAS: 78-93-3	<b>Butanone</b>	<b>2,5 - &lt;5 %</b>
CAS: 79-20-9	<b>methyl acetate</b>	<b>2,5 - &lt;5 %</b>
CAS: 108-65-6	<b>2-methoxy-1-methylethyl acetate</b>	<b>1 - &lt;2,5 %</b>
CAS: 67-56-1	<b>methanol</b>	<b>0,25 - &lt;1 %</b>

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

## SECTION 4: FIRST-AID MEASURES

**4.1 Description of necessary measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

- CONTINUED ON NEXT PAGE -

**SECTION 4: FIRST-AID MEASURES (continued)**

**4.2 Most important symptoms/effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Not applicable (N/A)

**SECTION 5: FIRE-FIGHTING MEASURES**

**5.1 Suitable (and unsuitable) extinguishing media:**

**Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and materials for containment and cleaning up:**

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

- CONTINUED ON NEXT PAGE -

**SECTION 7: HANDLING AND STORAGE (continued)**

**B.- Technical recommendations for the prevention of fires and explosions**

Because the product is a flammable liquid, storage should meet the requirement of 29 CFR 1910.106, Flammable and Combustible Liquids Code. Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations on general occupational hygiene**

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

**D.- Technical recommendations to prevent environmental risks**

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

**A.- Technical measures for storage**

Minimum Temp.: 41 °F

**B.- General conditions for storage**

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	400 ppm	1400 mg/m <sup>3</sup>
Ethyl acetate CAS: 141-78-6	Ceiling Values - TWA PEL		
Diocetyl tin dilaurate CAS: 3648-18-8	8-hour TWA PEL		0.1 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	8-hour TWA PEL	100 ppm	435 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
N-butyl acetate CAS: 123-86-4	8-hour TWA PEL	150 ppm	710 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
methanol CAS: 67-56-1	8-hour TWA PEL	200 ppm	260 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
methyl acetate CAS: 79-20-9	8-hour TWA PEL	200 ppm	610 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Butanone CAS: 78-93-3	8-hour TWA PEL	200 ppm	590 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
ethanol CAS: 64-17-5	8-hour TWA PEL	1000 ppm	1900 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Toluene CAS: 108-88-3	8-hour TWA PEL	200 ppm	300 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	8-hour TWA PEL	100 ppm	435 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Methyl methacrylate CAS: 80-62-6	8-hour TWA PEL	100 ppm	410 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-TWA	TLV-STEL	
Ethyl acetate CAS: 141-78-6	150 ppm		
Diocetyl tin dilaurate CAS: 3648-18-8			0.1 mg/m <sup>3</sup>
Amorphous silica gel CAS: 112926-00-8			4 mg/m <sup>3</sup>
Paraffin waxes and Hydrocarbon waxes CAS: 8002-74-2			2 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	100 ppm	150 ppm	
N-butyl acetate CAS: 123-86-4	20 ppm		
2-methoxy-1-methylethyl acetate CAS: 108-65-6	50 ppm	75 ppm	
2-methoxypropyl acetate CAS: 70657-70-4	20 ppm	40 ppm	
methanol CAS: 67-56-1	200 ppm	250 ppm	
methyl acetate CAS: 79-20-9	200 ppm	250 ppm	
Butanone CAS: 78-93-3	50 ppm	100 ppm	
ethanol CAS: 64-17-5		1000 ppm	
Toluene CAS: 108-88-3	20 ppm		
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	100 ppm	150 ppm	
Methyl methacrylate CAS: 80-62-6	50 ppm	100 ppm	

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
	PEL	STEL	
Ethyl acetate CAS: 141-78-6	400 ppm		1400 mg/m <sup>3</sup>
Diocetyl tin dilaurate CAS: 3648-18-8			0.1 mg/m <sup>3</sup>
Paraffin waxes and Hydrocarbon waxes CAS: 8002-74-2			2 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	100 ppm	150 ppm	435 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4	150 ppm	200 ppm	710 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6	100 ppm	811 ppm	541 mg/m <sup>3</sup>
methanol CAS: 67-56-1	200 ppm	250 ppm	260 mg/m <sup>3</sup>
methyl acetate CAS: 79-20-9	200 ppm	250 ppm	610 mg/m <sup>3</sup>
ethanol CAS: 64-17-5	1000 ppm		1900 mg/m <sup>3</sup>
Toluene CAS: 108-88-3	10 ppm	150 ppm	37 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	100 ppm	150 ppm	435 mg/m <sup>3</sup>

Biological limit values:

Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	1500 mg/g (NULL)	Methylhippuric acids in urine	End of shift

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Biological Exposure Indices (BEIs®) - ACGIH


Identification	BEIs®	Determinant	Sampling Time
methanol CAS: 67-56-1	15 mg/L	Methanol in urine	End of shift
Butanone CAS: 78-93-3	2 mg/L	Methyl ethyl ketone in urine	End of shift
Toluene CAS: 108-88-3	0.02 mg/L	Toluene in blood	Prior to last shift of workweek
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	1500 mg/g (NULL)	Methylhippuric acids in urine	End of shift

8.2 Appropriate engineering controls:


A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR).

C.- Specific protection for the hands



Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)



E.- Bodily protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**40 CFR Part 59 (VOC):**

V.O.C.(weight-percent): 76.41 % weight  
V.O.C. at 77 °F: 733.62 kg/m<sup>3</sup> (733.62 g/L)

**California Air Resources Board (CARB) - VOC Regulatory:**

V.O.C.(weight-percent): 76.41 % weight  
V.O.C. at 77 °F: 733.62 kg/m<sup>3</sup> (733.62 g/L)

**South Coast Air Quality Management District (AQMD) - VOC Regulatory:**

V.O.C.(weight-percent): 76.41 % weight  
V.O.C. at 77 °F: 733.62 kg/m<sup>3</sup> (733.62 g/L)

**Ozone Transport Commission (OTC) Rules - VOC Regulatory:**

V.O.C.(weight-percent): 76.41 % weight  
V.O.C. at 77 °F: 733.62 kg/m<sup>3</sup> (733.62 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 68 °F: Liquid  
Appearance: Viscous  
Color: Not available  
Odor: Not available  
Odour threshold: Not applicable (N/A) \*

**Volatility:**

Boiling point at atmospheric pressure: 211 °F  
Vapour pressure at 77 °F: 7962 Pa  
Vapour pressure at 122 °F: 24019.73 Pa (24.02 kPa)  
Evaporation rate at 77 °F: Not applicable (N/A) \*

**Product description:**

Density at 77 °F: 927.9 kg/m<sup>3</sup>  
Relative density at 77 °F: 0.928  
Dynamic viscosity at 77 °F: Not applicable (N/A) \*  
Kinematic viscosity at 77 °F: Not applicable (N/A) \*  
Kinematic viscosity at 104 °F: >20.5 mm<sup>2</sup>/s  
Concentration: Not applicable (N/A) \*  
pH: Not applicable (N/A) \*  
Vapour density at 77 °F: Not applicable (N/A) \*  
Partition coefficient n-octanol/water 77 °F: Not applicable (N/A) \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Solubility in water at 77 °F: Not applicable (N/A) \*  
 Solubility properties: Not applicable (N/A) \*  
 Decomposition temperature: Not applicable (N/A) \*  
 Melting point/freezing point: Not applicable (N/A) \*

**Flammability:**

Flash Point: 63 °F  
 Flammability (solid, gas): Not applicable (N/A) \*  
 Autoignition temperature: 446 °F  
 Lower flammability limit: Not available  
 Upper flammability limit: Not available

**Particle characteristics:**

Median equivalent diameter: Non-applicable

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties: Not applicable (N/A) \*  
 Oxidising properties: Not applicable (N/A) \*  
 Corrosive to metals: Not applicable (N/A) \*  
 Heat of combustion: Not applicable (N/A) \*  
 Aerosols-total percentage (by mass) of flammable components: Not applicable (N/A) \*

**Other safety characteristics:**

Surface tension at 77 °F: Not applicable (N/A) \*  
 Refraction index: Not applicable (N/A) \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Polyethylene wax (3); Reaction mass of ethylbenzene and m-xylene and p-xylene (3); (3); ethanol (1); Toluene (3); Reaction mass of ethylbenzene and xylene (3); Methyl methacrylate (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not applicable (N/A)

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
Ethyl acetate CAS: 141-78-6	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (ATEI)	

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
N-butyl acetate CAS: 123-86-4	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23.4 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
methanol CAS: 67-56-1	LD50 oral	100 mg/kg	
	LD50 dermal	300 mg/kg	
	LC50 inhalation	3 mg/L (4 h)	Rat
methyl acetate CAS: 79-20-9	LD50 oral	6482 mg/kg	Rat
	LD50 dermal	18684 mg/kg	Guinean pig
	LC50 inhalation	75 mg/L (4 h)	Rabbit
Butanone CAS: 78-93-3	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23.5 mg/L (4 h)	Rat
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration		Species	Genus
N-butyl acetate CAS: 123-86-4	LC50	Not applicable (N/A)		
	EC50	Not applicable (N/A)		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Ethyl acetate CAS: 141-78-6	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Butanone CAS: 78-93-3	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
methyl acetate CAS: 79-20-9	LC50	320 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1026.7 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	120 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Not applicable (N/A)		
methanol CAS: 67-56-1	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	12000 mg/L (96 h)	Nitrocra spinipes	Crustacean
	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
N-butyl acetate CAS: 123-86-4	NOEC	Not applicable (N/A)		
	NOEC	23.2 mg/L	Daphnia magna	Crustacean
Ethyl acetate CAS: 141-78-6	NOEC	9.65 mg/L	Pimephales promelas	Fish
	NOEC	2.4 mg/L	Daphnia magna	Crustacean
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	NOEC	1.3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1.17 mg/L	Ceriodaphnia dubia	Crustacean

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	NOEC	1.3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1.17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6	NOEC	47.5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean
methanol CAS: 67-56-1	NOEC	15800 mg/L	Oryzias latipes	Fish
	NOEC	122 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
N-butyl acetate CAS: 123-86-4	BOD5	Not applicable (N/A)	Concentration	Not applicable (N/A)
	COD	Not applicable (N/A)	Period	5 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	84 %
Ethyl acetate CAS: 141-78-6	BOD5	1.36 g O2/g	Concentration	100 mg/L
	COD	1.69 g O2/g	Period	14 days
	BOD5/COD	0.8	% Biodegradable	83 %
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	BOD5	Not applicable (N/A)	Concentration	Not applicable (N/A)
	COD	Not applicable (N/A)	Period	28 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	88 %
Butanone CAS: 78-93-3	BOD5	2.03 g O2/g	Concentration	Not applicable (N/A)
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
methyl acetate CAS: 79-20-9	BOD5	Not applicable (N/A)	Concentration	100 mg/L
	COD	Not applicable (N/A)	Period	14 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	92 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6	BOD5	Not applicable (N/A)	Concentration	785 mg/L
	COD	Not applicable (N/A)	Period	8 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	100 %
methanol CAS: 67-56-1	BOD5	Not applicable (N/A)	Concentration	100 mg/L
	COD	1.42 g O2/g	Period	14 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
N-butyl acetate CAS: 123-86-4	BCF	4
	Pow Log	1.78
	Potential	Low
Ethyl acetate CAS: 141-78-6	BCF	30
	Pow Log	0.73
	Potential	Moderate
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	BCF	9
	Pow Log	2.77
	Potential	Low

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	BCF	9
	Pow Log	2.77
	Potential	Low
Butanone CAS: 78-93-3	BCF	3
	Pow Log	0.29
	Potential	Low
methyl acetate CAS: 79-20-9	BCF	0.8
	Pow Log	0.18
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6	BCF	1
	Pow Log	0.43
	Potential	Low
methanol CAS: 67-56-1	BCF	3
	Pow Log	-0.77
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
N-butyl acetate CAS: 123-86-4	Koc	Not applicable (N/A)	Henry	Not applicable (N/A)
	Conclusion	Not applicable (N/A)	Dry soil	Not applicable (N/A)
	Surface tension	2.478E-2 N/m (77 °F)	Moist soil	Not applicable (N/A)
Ethyl acetate CAS: 141-78-6	Koc	59	Henry	13.58 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.324E-2 N/m (77 °F)	Moist soil	Yes
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	Koc	202	Henry	524.86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Not applicable (N/A)	Moist soil	Yes
Butanone CAS: 78-93-3	Koc	30	Henry	5.77 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.396E-2 N/m (77 °F)	Moist soil	Yes
methyl acetate CAS: 79-20-9	Koc	Not applicable (N/A)	Henry	Not applicable (N/A)
	Conclusion	Not applicable (N/A)	Dry soil	Not applicable (N/A)
	Surface tension	2.454E-2 N/m (77 °F)	Moist soil	Not applicable (N/A)
methanol CAS: 67-56-1	Koc	Not applicable (N/A)	Henry	Not applicable (N/A)
	Conclusion	Not applicable (N/A)	Dry soil	Not applicable (N/A)
	Surface tension	2.355E-2 N/m (77 °F)	Moist soil	Not applicable (N/A)

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

The characteristic of Ignitability per RCRA could apply to the unused product if it becomes a waste material. The EPA hazardous waste number D001 could apply.

**Waste management (disposal and evaluation):**

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

**Regulations related to waste management:**

Legislation related to waste management:

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

40 CFR Solid Wastes - Part 239 through 282.  
State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

**Transport of dangerous goods by land:**

With regard to 49 CFR on the Transport of Dangerous Goods:



- 14.1 **UN number:** UN1263
- 14.2 **UN proper shipping name:** PAINT
- 14.3 **Transport hazard class(es):** 3  
Labels: 3
- 14.4 **Packing group, if applicable:** II
- 14.5 **Marine pollutant:** No
- 14.6 **Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L
- 14.7 **Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:



- 14.1 **UN number:** UN1263
- 14.2 **UN proper shipping name:** PAINT
- 14.3 **Transport hazard class(es):** 3  
Labels: 3
- 14.4 **Packing group, if applicable:** II
- 14.5 **Marine pollutant:** No
- 14.6 **Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Special regulations: 367, 163  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Not applicable (N/A)
- 14.7 **Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2023:



- 14.1 **UN number:** UN1263
- 14.2 **UN proper shipping name:** PAINT
- 14.3 **Transport hazard class(es):** 3  
Labels: 3
- 14.4 **Packing group, if applicable:** II
- 14.5 **Marine pollutant:** No
- 14.6 **Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
Physico-Chemical properties: see section 9
- 14.7 **Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

- CONTINUED ON NEXT PAGE -

## 130040 - AC Self-Sealer 0040 SMMT

## SECTION 15: REGULATORY INFORMATION

**15.1 Safety, health and environmental regulations specific for the product in question:**

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Reaction mass of ethylbenzene and xylene (Non-applicable)*; *Butanone (78-93-3)*; *methyl acetate (79-20-9)*; *methanol (67-56-1)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: *methanol (67-56-1)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Not applicable (N/A)
- CANADA-Domestic Substances List (DSL): *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *methyl acetate (79-20-9)*; *2-methoxy-1-methylethyl acetate (108-65-6)*; *methanol (67-56-1)*
- CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
- Hazardous Air Pollutants (Clean Air Act): *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *methanol (67-56-1)*
- Massachusetts RTK - Substance List: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Reaction mass of ethylbenzene and xylene (Non-applicable)*; *Butanone (78-93-3)*; *methyl acetate (79-20-9)*; *methanol (67-56-1)*
- Minnesota - Hazardous substances ERTK: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Reaction mass of ethylbenzene and xylene (Non-applicable)*; *Butanone (78-93-3)*; *methyl acetate (79-20-9)*; *methanol (67-56-1)*
- New Jersey Worker and Community Right-to-Know Act: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Reaction mass of ethylbenzene and xylene (Non-applicable)*; *Butanone (78-93-3)*; *methyl acetate (79-20-9)*; *methanol (67-56-1)*
- New York RTK - Substance list: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Reaction mass of ethylbenzene and xylene (Non-applicable)*; *Butanone (78-93-3)*; *methyl acetate (79-20-9)*; *methanol (67-56-1)*
- NTP (National Toxicology Program): Not applicable (N/A)
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Not applicable (N/A)
- Pennsylvania Worker and Community Right-to-Know Law: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *methyl acetate (79-20-9)*; *methanol (67-56-1)*
- Rhode Island - Hazardous substances RTK: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *methanol (67-56-1)*
- The Toxic Substances Control Act (TSCA) : *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *methyl acetate (79-20-9)*; *2-methoxy-1-methylethyl acetate (108-65-6)*; *methanol (67-56-1)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *methanol (67-56-1)*
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *N-butyl acetate (5000 pounds)*; *Ethyl acetate (5000 pounds)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (100 pounds)*; *Butanone (5000 pounds)*; *methanol (5000 pounds)*

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

Take into consideration other applicable federal, state, and local laws and local regulations.

## SECTION 16: OTHER INFORMATION

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

**Texts of the legislative phrases mentioned in section 2:**

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H315: Causes skin irritation.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H225: Highly flammable liquid and vapour.

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

- CONTINUED ON NEXT PAGE -

## SECTION 16: OTHER INFORMATION (continued)

Occupational Safety & Health Administration (OSHA).

**Abbreviations and acronyms:**

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 10/3/2019

Revised: 3/7/2023

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET