

190070	AC Hardener 070
--------	-----------------

Hardener for Acrylic products

### FEATURES

Properties	Non yellowing	Elastic	Good Çadherence
Recommended use	For Acrylic PU	Primers according to specification	
Application method			
Recommended Hardeners			
Diluyentes Recs.			

### AVAILABLE GLOSSES


### TYPICAL DATA (25 °C)

Density (Kg/L)	0.965 - 1.000		
MNV (%)	39 - 43		
VOCs (% Weight)	57.89		

### GENERAL FEATURES


### SUBSTRATE PREPARATION

### APLICATION ADVICES


### PRECAUTIONS

Check the can properly closed after using the product, unless it will get spoiled due to its reactivity whith enviromental humidity. Once the can is opened, it ought to be used as soon as possible.

We recommend to keep the product at a temperature between 5 and 35°C, avoidejng direct sun exposures of the containers.

Expiry date: 6 months (Under mentioned conditions).

Check TDS of the fir component.

With regard to the danger and toxicity of this product before using it, we advise you to read irjts MSDS

### ADDITIVES


THE FIGURES IN THIS DOCUMENT SHOULD BE UNDERSTOOD AS A GUIDANCE AND NOT AS A SALES SPECIFICATION.

**Note:** The aforementioned data and the advices we give verbally, in writing or through tests, have been carried out following our loyal knowledge and mind, nevertheless they are considered as mere advices and indications without any obligation, and also with regard to the possible third party industrial property rights. Our advice does not exempt you from doing tests to the indications we may give you or to the products we may provide you, in order to check if these products are the suitable for the purposes indicated. The application, use and transformation of our products and of the products you manufacture under our technical advice will be made out of our vigilance and therefore will be of your sole responsibility. The sale of our products is under our Selling and Delivery General Conditions. **07-03-2022\_Version-3**

**VALRESA.** Polígono Industrial Reva  
 Avda. dels Gremis, s/n Sector 13  
 Riba-Roja de Turia Valencia E46394  
 ESPAÑA Tel. 96 1669560