


SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** 210103 - NC White Sealer 103
Other means of identification:
Not applicable (N/A)
- 1.2 Recommended use of the chemical and restrictions on use:**
Relevant uses: Coatings for wood. For industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**
Valresa Coatings, S.A.
Pol. Ind. Reva S-13 Avda. dels Gremis s/n
46190 Riba-roja de Turia - Valencia - Spain
Phone: +34 961669560 - Fax: +34 961668665
safety@valresa.com
www.valresa.com
- 1.4 Emergency phone number:** +1 772 284 5590 (Only available during office hours)

SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
29 CFR 1910.1200:
Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.
Carc. 2: Carcinogenicity, Category 2, H351
Eye Irrit. 2A: Eye irritation, Category 2A, H319
Flam. Liq. 2: Flammable liquids, Category 2, H225
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
29 CFR 1910.1200:
Danger
- 
- Hazard statements:**
Suspected of causing cancer.
Causes serious eye irritation.
Highly flammable liquid and vapour.
May cause an allergic skin reaction.
May cause damage to organs through prolonged or repeated exposure (Oral).
May cause drowsiness or dizziness.
- Precautionary statements:**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
In case of fire: Use ABC powder extinguisher to put it out.
Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Substances that contribute to the classification**
N-butyl acetate; Ethyl acetate; Xylene; propan-2-ol
- Additional labeling:**



WARNING

- CONTINUED ON NEXT PAGE -

210103 - NC White Sealer 103

SECTION 2: HAZARD(S) IDENTIFICATION (continued)

This product can expose you to chemicals including Ethylbenzene, which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

2.3 Hazards not otherwise classified (HNOC):

Not applicable (N/A)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Mixture composed of nitrocelluloses, pigments, plasticizers and resins in solvents

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name	Concentration
CAS: 123-86-4	N-butyl acetate	10 - <25 %
CAS: 141-78-6	Ethyl acetate	5 - <10 %
CAS: 1330-20-7	Xylene	5 - <10 %
CAS: 67-63-0	propan-2-ol	5 - <10 %
CAS: Non-applicable	Reaction mass of ethylbenzene and m-xylene and p-xylene	2,5 - <5 %
CAS: 78-93-3	Butanone	2,5 - <5 %
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	1 - <2,5 %
CAS: 100-41-4	Ethylbenzene	0,25 - <1 %
CAS: 85711-46-2	Fatty acids, C14-18 and C16-18-unsatd., maleated	<0,25 %
CAS: 108-31-6	maleic anhydride	<0,25 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

- CONTINUED ON NEXT PAGE -

SECTION 4: FIRST-AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not applicable (N/A)

SECTION 5: FIRE-FIGHTING MEASURES**5.1 Suitable (and unsuitable) extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -

210103 - NC White Sealer 103

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Because the product is a flammable liquid, storage should meet the requirement of 29 CFR 1910.106, Flammable and Combustible Liquids Code. Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 41 °F

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	400 ppm	980 mg/m ³
propan-2-ol CAS: 67-63-0	Ceiling Values - TWA PEL		
N-butyl acetate CAS: 123-86-4	8-hour TWA PEL	150 ppm	710 mg/m ³
	Ceiling Values - TWA PEL		
Butanone CAS: 78-93-3	8-hour TWA PEL	200 ppm	590 mg/m ³
	Ceiling Values - TWA PEL		
Titanium dioxide (aerodynamic diameter ≥ 10 µm) CAS: 13463-67-7	8-hour TWA PEL		15 mg/m ³
	Ceiling Values - TWA PEL		
Zirconium dioxide CAS: 1314-23-4	8-hour TWA PEL		5 mg/m ³
	Ceiling Values - TWA PEL		
Ethyl acetate CAS: 141-78-6	8-hour TWA PEL	400 ppm	1400 mg/m ³
	Ceiling Values - TWA PEL		
phthalic anhydride CAS: 85-44-9	8-hour TWA PEL	2 ppm	12 mg/m ³
	Ceiling Values - TWA PEL		
Xylene CAS: 1330-20-7	8-hour TWA PEL	100 ppm	435 mg/m ³
	Ceiling Values - TWA PEL		
Ethylbenzene	8-hour TWA PEL	100 ppm	435 mg/m ³

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	200 ppm	300 mg/m ³
CAS: 100-41-4	Ceiling Values - TWA PEL		
Toluene	8-hour TWA PEL	200 ppm	300 mg/m ³
CAS: 108-88-3	Ceiling Values - TWA PEL		
Reaction mass of ethylbenzene and m-xylene and p-xylene	8-hour TWA PEL	100 ppm	435 mg/m ³
CAS: Non-applicable	Ceiling Values - TWA PEL		
Phosphoric acid	8-hour TWA PEL		1 mg/m ³
CAS: 7664-38-2	Ceiling Values - TWA PEL		
Ethylbenzene	8-hour TWA PEL	100 ppm	435 mg/m ³
CAS: 100-41-4	Ceiling Values - TWA PEL		
2,6-dimethylheptan-4-one	8-hour TWA PEL	50 ppm	290 mg/m ³
CAS: 108-83-8	Ceiling Values - TWA PEL		
maleic anhydride	8-hour TWA PEL	0.25 ppm	1 mg/m ³
CAS: 108-31-6	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-TWA	TLV-STEL	TLV-TWA
propan-2-ol	TLV-TWA	200 ppm	
CAS: 67-63-0	TLV-STEL	400 ppm	
N-butyl acetate	TLV-TWA	20 ppm	
CAS: 123-86-4	TLV-STEL		
Butanone	TLV-TWA	50 ppm	
CAS: 78-93-3	TLV-STEL	100 ppm	
Talc	TLV-TWA		2 mg/m ³
CAS: 14807-96-6	TLV-STEL		
Zinc distearate	TLV-TWA		10 mg/m ³
CAS: 557-05-1	TLV-STEL		20 mg/m ³
Titanium dioxide (aerodynamic diameter ≥ 10 µm)	TLV-TWA		2.5 mg/m ³
CAS: 13463-67-7	TLV-STEL		
Aluminum Oxide	TLV-TWA		1 mg/m ³
CAS: 1344-28-1	TLV-STEL		
Zirconium dioxide	TLV-TWA		5 mg/m ³
CAS: 1314-23-4	TLV-STEL		10 mg/m ³
Ethyl acetate	TLV-TWA	150 ppm	
CAS: 141-78-6	TLV-STEL		
phthalic anhydride	TLV-TWA	1 ppm	
CAS: 85-44-9	TLV-STEL		
Xylene	TLV-TWA	100 ppm	
CAS: 1330-20-7	TLV-STEL	150 ppm	
Ethylbenzene	TLV-TWA	20 ppm	
CAS: 100-41-4	TLV-STEL		
Toluene	TLV-TWA	20 ppm	
CAS: 108-88-3	TLV-STEL		
Reaction mass of ethylbenzene and m-xylene and p-xylene	TLV-TWA	100 ppm	
CAS: Non-applicable	TLV-STEL	150 ppm	
Phosphoric acid	TLV-TWA		1 mg/m ³
CAS: 7664-38-2	TLV-STEL		3 mg/m ³
2-methoxy-1-methylethyl acetate	TLV-TWA	50 ppm	
CAS: 108-65-6	TLV-STEL	75 ppm	
2-methoxypropyl acetate	TLV-TWA	20 ppm	
CAS: 70657-70-4	TLV-STEL	40 ppm	
Limestone	TLV-TWA		10 mg/m ³
CAS: 1317-65-3	TLV-STEL		20 mg/m ³
Ethylbenzene	TLV-TWA	20 ppm	
CAS: 100-41-4	TLV-STEL		
2,6-dimethylheptan-4-one	TLV-TWA	25 ppm	
CAS: 108-83-8	TLV-STEL		

- CONTINUED ON NEXT PAGE -

210103 - NC White Sealer 103

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
maleic anhydride CAS: 108-31-6	TLV-TWA	0.1 ppm	
	TLV-STEL		

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
propan-2-ol CAS: 67-63-0	PEL	400 ppm	980 mg/m ³
	STEL	500 ppm	1225 mg/m ³
N-butyl acetate CAS: 123-86-4	PEL	150 ppm	710 mg/m ³
	STEL	200 ppm	950 mg/m ³
Talc CAS: 14807-96-6	PEL		2 mg/m ³
	STEL		
Zinc distearate CAS: 557-05-1	PEL		10 mg/m ³
	STEL		
Aluminum Oxide CAS: 1344-28-1	PEL		2 mg/m ³
	STEL		
Zirconium dioxide CAS: 1314-23-4	PEL		5 mg/m ³
	STEL		10 mg/m ³
Ethyl acetate CAS: 141-78-6	PEL	400 ppm	1400 mg/m ³
	STEL		
phthalic anhydride CAS: 85-44-9	PEL	1 ppm	6 mg/m ³
	STEL		
Xylene CAS: 1330-20-7	PEL	100 ppm	435 mg/m ³
	STEL	150 ppm	655 mg/m ³
Ethylbenzene CAS: 100-41-4	PEL	5 ppm	22 mg/m ³
	STEL	30 ppm	130 mg/m ³
Toluene CAS: 108-88-3	PEL	10 ppm	37 mg/m ³
	STEL	150 ppm	560 mg/m ³
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	PEL	100 ppm	435 mg/m ³
	STEL	150 ppm	655 mg/m ³
Phosphoric acid CAS: 7664-38-2	PEL		1 mg/m ³
	STEL		3 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6	PEL	100 ppm	541 mg/m ³
	STEL	811 ppm	
Ethylbenzene CAS: 100-41-4	PEL	5 ppm	22 mg/m ³
	STEL	30 ppm	130 mg/m ³
2,6-dimethylheptan-4-one CAS: 108-83-8	PEL	25 ppm	150 mg/m ³
	STEL		
maleic anhydride CAS: 108-31-6	PEL	0.1 ppm	0.4 mg/m ³
	STEL		

Biological limit values:

Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
propan-2-ol CAS: 67-63-0	40 mg/L	Acetone in urine	End of shift at end of workweek
Butanone CAS: 78-93-3	2 mg/L	Methyl ethyl ketone in urine	End of shift
Xylene CAS: 1330-20-7	1500 mg/g (NULL)	Methylhippuric acids in urine	End of shift
Ethylbenzene CAS: 100-41-4	150 mg/g (NULL)	Sum of mandelic acid and phenylglyoxylic acid in urine	End of shift
Toluene CAS: 108-88-3	0.02 mg/L	Toluene in blood	Prior to last shift of workweek
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	1500 mg/g (NULL)	Methylhippuric acids in urine	End of shift
Ethylbenzene CAS: 100-41-4	150 mg/g (NULL)	Sum of mandelic acid and phenylglyoxylic acid in urine	End of shift

8.2 Appropriate engineering controls:

- CONTINUED ON NEXT PAGE -


210103 - NC White Sealer 103

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)


A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR).

C.- Specific protection for the hands



Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

40 CFR Part 59 (VOC):

V.O.C.(weight-percent):	42.36 % weight
V.O.C. at 77 °F:	530.36 kg/m ³ (530.36 g/L)

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

California Air Resources Board (CARB) - VOC Regulatory:

V.O.C.(weight-percent):	42.36 % weight
V.O.C. at 77 °F:	530.36 kg/m ³ (530.36 g/L)

South Coast Air Quality Management District (AQMD) - VOC Regulatory:

V.O.C.(weight-percent):	42.36 % weight
V.O.C. at 77 °F:	530.36 kg/m ³ (530.36 g/L)

Ozone Transport Commission (OTC) Rules - VOC Regulatory:

V.O.C.(weight-percent):	42.36 % weight
V.O.C. at 77 °F:	530.36 kg/m ³ (530.36 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F:	Liquid
Appearance:	Viscous
Color:	White
Odor:	Not available
Odour threshold:	Not applicable (N/A) *

Volatility:

Boiling point at atmospheric pressure:	226 °F
Vapour pressure at 77 °F:	5042 Pa
Vapour pressure at 122 °F:	16522.59 Pa (16.52 kPa)
Evaporation rate at 77 °F:	Not applicable (N/A) *

Product description:

Density at 77 °F:	1251.9 kg/m ³
Relative density at 77 °F:	1.252
Dynamic viscosity at 77 °F:	Not applicable (N/A) *
Kinematic viscosity at 77 °F:	171 mm ² /s
Kinematic viscosity at 104 °F:	>20.5 mm ² /s
Concentration:	Not applicable (N/A) *
pH:	Not applicable (N/A) *
Vapour density at 77 °F:	Not applicable (N/A) *
Partition coefficient n-octanol/water 77 °F:	Not applicable (N/A) *
Solubility in water at 77 °F:	Not applicable (N/A) *
Solubility properties:	Not applicable (N/A) *
Decomposition temperature:	Not applicable (N/A) *
Melting point/freezing point:	Not applicable (N/A) *

Flammability:

Flash Point:	60 °F
Flammability (solid, gas):	Not applicable (N/A) *
Autoignition temperature:	599 °F
Lower flammability limit:	Not available
Upper flammability limit:	Not available

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Not applicable (N/A) *

Oxidising properties: Not applicable (N/A) *

Corrosive to metals: Not applicable (N/A) *

Heat of combustion: Not applicable (N/A) *

Aerosols-total percentage (by mass) of flammable components: Not applicable (N/A) *

Other safety characteristics:

Surface tension at 77 °F: Not applicable (N/A) *

Refraction index: Not applicable (N/A) *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- CONTINUED ON NEXT PAGE -

210103 - NC White Sealer 103

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
IARC: propan-2-ol (3); Talc (3); Xylene (3); Ethylbenzene (2B); Toluene (3); Reaction mass of ethylbenzene and m-xylene and p-xylene (3); Hydrocarbons, C9, aromatics (3); (3); Ethylbenzene (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not applicable (N/A)

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
propan-2-ol CAS: 67-63-0	LD50 oral	5280 mg/kg	Rat
	LD50 dermal	12800 mg/kg	Rat
	LC50 inhalation	72.6 mg/L (4 h)	Rat
N-butyl acetate CAS: 123-86-4	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23.4 mg/L (4 h)	Rat
Butanone CAS: 78-93-3	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23.5 mg/L (4 h)	Rat
Ethyl acetate CAS: 141-78-6	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
Xylene CAS: 1330-20-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (ATEI)	

- CONTINUED ON NEXT PAGE -

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (ATEI)	
2-methoxy-1-methylethyl acetate CAS: 108-65-6	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Ethylbenzene CAS: 100-41-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17.2 mg/L (4 h)	Rat
Fatty acids, C14-18 and C16-18-unsatd., maleated CAS: 85711-46-2	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
maleic anhydride CAS: 108-31-6	LD50 oral	1090 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration		Species	Genus
N-butyl acetate CAS: 123-86-4	LC50	Not applicable (N/A)		
	EC50	Not applicable (N/A)		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Ethyl acetate CAS: 141-78-6	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
propan-2-ol CAS: 67-63-0	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
Butanone CAS: 78-93-3	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Not applicable (N/A)		
Ethylbenzene CAS: 100-41-4	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
N-butyl acetate CAS: 123-86-4	NOEC	Not applicable (N/A)		
	NOEC	23.2 mg/L	Daphnia magna	Crustacean
Ethyl acetate CAS: 141-78-6	NOEC	9.65 mg/L	Pimephales promelas	Fish
	NOEC	2.4 mg/L	Daphnia magna	Crustacean
Xylene CAS: 1330-20-7	NOEC	1.3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1.17 mg/L	Ceriodaphnia dubia	Crustacean
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	NOEC	1.3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1.17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6	NOEC	47.5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean

- CONTINUED ON NEXT PAGE -

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Ethylbenzene CAS: 100-41-4	NOEC	Not applicable (N/A)		
	NOEC	0.96 mg/L	Ceriodaphnia dubia	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
N-butyl acetate CAS: 123-86-4	BOD5	Not applicable (N/A)	Concentration	Not applicable (N/A)
	COD	Not applicable (N/A)	Period	5 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	84 %
Ethyl acetate CAS: 141-78-6	BOD5	1.36 g O2/g	Concentration	100 mg/L
	COD	1.69 g O2/g	Period	14 days
	BOD5/COD	0.8	% Biodegradable	83 %
Xylene CAS: 1330-20-7	BOD5	Not applicable (N/A)	Concentration	Not applicable (N/A)
	COD	Not applicable (N/A)	Period	28 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	88 %
propan-2-ol CAS: 67-63-0	BOD5	1.19 g O2/g	Concentration	100 mg/L
	COD	2.23 g O2/g	Period	14 days
	BOD5/COD	0.53	% Biodegradable	86 %
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	BOD5	Not applicable (N/A)	Concentration	Not applicable (N/A)
	COD	Not applicable (N/A)	Period	28 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	88 %
Butanone CAS: 78-93-3	BOD5	2.03 g O2/g	Concentration	Not applicable (N/A)
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6	BOD5	Not applicable (N/A)	Concentration	785 mg/L
	COD	Not applicable (N/A)	Period	8 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	100 %
Ethylbenzene CAS: 100-41-4	BOD5	Not applicable (N/A)	Concentration	100 mg/L
	COD	Not applicable (N/A)	Period	14 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	90 %
maleic anhydride CAS: 108-31-6	BOD5	Not applicable (N/A)	Concentration	33.33 mg/L
	COD	Not applicable (N/A)	Period	29 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	98.19 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
N-butyl acetate CAS: 123-86-4	BCF	4
	Pow Log	1.78
	Potential	Low
Ethyl acetate CAS: 141-78-6	BCF	30
	Pow Log	0.73
	Potential	Moderate

- CONTINUED ON NEXT PAGE -

210103 - NC White Sealer 103

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
Xylene CAS: 1330-20-7	BCF	9
	Pow Log	2.77
	Potential	Low
propan-2-ol CAS: 67-63-0	BCF	3
	Pow Log	0.05
	Potential	Low
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	BCF	9
	Pow Log	2.77
	Potential	Low
Butanone CAS: 78-93-3	BCF	3
	Pow Log	0.29
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6	BCF	1
	Pow Log	0.43
	Potential	Low
Ethylbenzene CAS: 100-41-4	BCF	1
	Pow Log	3.15
	Potential	Low
maleic anhydride CAS: 108-31-6	BCF	
	Pow Log	-2.61
	Potential	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Not applicable (N/A)	Henry	Not applicable (N/A)
N-butyl acetate CAS: 123-86-4	Conclusion	Not applicable (N/A)	Dry soil	Not applicable (N/A)
	Surface tension	2.478E-2 N/m (77 °F)	Moist soil	Not applicable (N/A)
	Koc	59	Henry	13.58 Pa·m ³ /mol
Ethyl acetate CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.324E-2 N/m (77 °F)	Moist soil	Yes
	Koc	202	Henry	524.86 Pa·m ³ /mol
Xylene CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Not applicable (N/A)	Moist soil	Yes
	Koc	1.5	Henry	8.207E-1 Pa·m ³ /mol
propan-2-ol CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.24E-2 N/m (77 °F)	Moist soil	Yes
	Koc	202	Henry	524.86 Pa·m ³ /mol
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Not applicable (N/A)	Moist soil	Yes
	Koc	30	Henry	5.77 Pa·m ³ /mol
Butanone CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.396E-2 N/m (77 °F)	Moist soil	Yes
	Koc	520	Henry	798.44 Pa·m ³ /mol
Ethylbenzene CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2.859E-2 N/m (77 °F)	Moist soil	Yes
	Koc	42	Henry	0E+0 Pa·m ³ /mol
maleic anhydride CAS: 108-31-6	Conclusion	Very High	Dry soil	Not applicable (N/A)
	Surface tension	1.673E-2 N/m (482.38 °F)	Moist soil	Not applicable (N/A)

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

- CONTINUED ON NEXT PAGE -

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

The characteristic of Ignitability per RCRA could apply to the unused product if it becomes a waste material. The EPA hazardous waste number D001 could apply.

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



- 14.1 UN number: UN1263
- 14.2 UN proper shipping name: PAINT
- 14.3 Transport hazard class(es): 3
Labels: 3
- 14.4 Packing group, if applicable: III
- 14.5 Marine pollutant: No
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number: UN1263
- 14.2 UN proper shipping name: PAINT
- 14.3 Transport hazard class(es): 3
Labels: 3
- 14.4 Packing group, if applicable: III
- 14.5 Marine pollutant: No
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Special regulations: 223, 955, 163, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Not applicable (N/A)
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

210103 - NC White Sealer 103

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number:	UN1263
14.2 UN proper shipping name:	PAINT
14.3 Transport hazard class(es):	3
Labels:	3
14.4 Packing group, if applicable:	III
14.5 Marine pollutant:	No
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises	
Physico-Chemical properties:	see section 9
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Not applicable (N/A)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Not applicable (N/A)
 - California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: *Ethylbenzene (100-41-4)*
 - CANADA-Domestic Substances List (DSL): *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *2-methoxy-1-methylethyl acetate (108-65-6)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - CANADA-Non-Domestic Substances List (NDSL): *Fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)*
 - Hazardous Air Pollutants (Clean Air Act): *Xylene (1330-20-7)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - Massachusetts RTK - Substance List: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - Minnesota - Hazardous substances ERTK: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - New Jersey Worker and Community Right-to-Know Act: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - New York RTK - Substance list: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - NTP (National Toxicology Program): Not applicable (N/A)
 - OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Not applicable (N/A)
 - Pennsylvania Worker and Community Right-to-Know Law: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - Rhode Island - Hazardous substances RTK: *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
 - The Toxic Substances Control Act (TSCA) : *N-butyl acetate (123-86-4)*; *Ethyl acetate (141-78-6)*; *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Butanone (78-93-3)*; *2-methoxy-1-methylethyl acetate (108-65-6)*; *Ethylbenzene (100-41-4)*; *Fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)*; *maleic anhydride (108-31-6)*
 - Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *Xylene (1330-20-7)*; *propan-2-ol (67-63-0)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (Non-applicable)*; *Ethylbenzene (100-41-4)*; *maleic anhydride (108-31-6)*
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *N-butyl acetate (5000 pounds)*; *Ethyl acetate (5000 pounds)*; *Xylene (100 pounds)*; *Reaction mass of ethylbenzene and m-xylene and p-xylene (100 pounds)*; *Butanone (5000 pounds)*; *Ethylbenzene (1000 pounds)*; *maleic anhydride (5000 pounds)*
- Specific provisions in terms of protecting people or the environment:**

- CONTINUED ON NEXT PAGE -

SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H317: May cause an allergic skin reaction.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H351: Suspected of causing cancer.

H225: Highly flammable liquid and vapour.

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 2/22/2017

Revised: 1/4/2023

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET