

500024

Solvent 0024 Slow PU

Disolvente lento para altas temperaturas

FEATURES

Properties	Low evaporación		
Recommended use	For high temperatures	High humidity	
Application method			
Recommended Hardeners			
Diluyentes Recs.			

AVAILABLE GLOSSES

TYPICAL DATA (25 °C)

Density (g/cm³)	0,9		
VOC content (% w)	100		

GENERAL FEATURES

SUBSTRATE PREPARATION

APPLICATION ADVICES

PRECAUTIONS

Expiry date: 1 year

Different solvents have different applications. Use every solvent for the purpose recommended for the manufacturer.

With regard to the danger and toxicity of this product before using it, we advise you to read its MSDS.

ADDITIVES

THE FIGURES IN THIS DOCUMENT SHOULD BE UNDERSTOOD AS A GUIDANCE AND NOT AS A SALES SPECIFICATION.

Note: The aforementioned data and the advices we give verbally, in writing or through tests, have been carried out following our loyal knowledge and mind, nevertheless they are considered as mere advices and indications without any obligation, and also with regard to the possible third party industrial property rights. Our advice does not exempt you from doing tests to the indications we may give you or to the products we may provide you, in order to check if these products are the suitable for the purposes indicated. The application, use and transformation of our products and of the products you manufacture under our technical advice will be made out of our vigilance and therefore will be of your sole responsibility. The sale of our products is under our Selling and Delivery General Conditions. **18-07-2022_Version-1**

VALRESA. Polígono Industrial Reva
 Avda. dels Gremis, s/n Sector 13
 Riba-Roja de Turia Valencia E46394
 ESPAÑA Tel. 96 1669560