

510107	Solvent 0107 PU Basic
--------	-----------------------

Solvent for PU

FEATURES

Properties	Balanced evaporation	Easy to sand	
Recommended use	PU sealers & topcoats		
Application method			
Recommended Hardeners			
Diluyentes Recs.			

AVAILABLE GLOSSES

TYPICAL DATA (25 °C)

Density (Kg/L)	0,865 - 0,895		
VOCs (% Weight)	100		

GENERAL FEATURES

SUBSTRATE PREPARATION

APPLICATION ADVICES

PRECAUTIONS

Keep containers containing the solvent closed when not being manipulated, unless the product will evaporate.
 With regard to the danger and toxicity of this product before using it, we advise you to read its MSDS.
 Different solvents have different applications. Use every solvent for the purpose recommended for the manufacturer.
 Expiry date: 1 year

ADDITIVES

THE FIGURES IN THIS DOCUMENT SHOULD BE UNDERSTOOD AS A GUIDANCE AND NOT AS A SALES SPECIFICATION.

Note: The aforementioned data and the advices we give verbally, in writing or through tests, have been carried out following our loyal knowledge and mind, nevertheless they are considered as mere advices and indications without any obligation, and also with regard to the possible third party industrial property rights. Our advice does not exempt you from doing tests to the indications we may give you or to the products we may provide you, in order to check if these products are the suitable for the purposes indicated. The application, use and transformation of our products and of the products you manufacture under our technical advice will be made out of our vigilance and therefore will be of your sole responsibility. The sale of our products is under our Selling and Delivery General Conditions. **06-04-2022_Version-2**

VALRESA. Polígono Industrial Reva
 Avda. dels Gremis, s/n Sector 13
 Riba-Roja de Turia Valencia E46394
 ESPAÑA Tel. 96 1669560